

# CRAFTERS CHOICE FABRIC GLUE

## Material Safety Data Sheet

### 1. Identification of Material and Supplier

**Product Name:** CRAFTERS CHOICE FABRIC GLUE

**Recommended Use:** High performance laminating adhesive designed to bond fabric and vinyls to various surfaces including MDF, paper, cardboard, styrene, glass and plastic

**Supplier:** CSA Trading Pty Ltd

**ABN:** 86 124 105 004

**Street Address:** 21-23 Joseph St  
Blackburn North  
Victoria, 3130  
Australia

**Telephone Number:** +61 3 9895 4333

**Facsimile:** +61 3 9899 4519

**Emergency Telephone:** (24 HOURS)

**Contact Poison Information Centre:** 13 11 26 (Australia) 0800 764 766 (New Zealand)

### 2. Hazards Identification

**NON HAZARDOUS SUBSTANCE. NON DANGEROUS GOODS.**

This material is NOT classified as Hazardous according to health criteria of NOHSC Australia.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

**Other information:** Repeated or prolonged skin contact can cause irritation and chronic dermatitis

### 3. Composition/Information on Ingredients

COMPOSITION	CAS #	%	Hazard Symbol	Risk Phrase
Synthetic polymer emulsion		70-90%		
Water	7732-18-5	5-15%		
Plasticiser		5-10%		
Toluene	108-88-3	1-3%	Xn, F	R11, R20

**Chemical characteristics:** Liquid

# CRAFTERS CHOICE FABRIC GLUE

## Material Safety Data Sheet

### 4. First-Aid Measures

For advice, contact a Poisons Information Centre (Phone: Australia 13 11 26; New Zealand 0800 764766) or a doctor.

- Inhalation:** Remove patient to fresh air. Recovery should be rapid after removal from exposure. Seek medical advice if symptoms persist.
- Skin:** Wash area(s) with copious quantities of water immediately. If irritation occurs seek medical attention. Remove contaminated clothing and wash before re-use
- Eye Contact:** Hold eyelids open and immediately flush eyes continuously with running water for 15 minutes. It is advisable to seek medical advice for all eye contaminations.
- Ingestion:** Rinse mouth thoroughly with water immediately. If swallowed do NOT induce vomiting. Give plenty of water to drink. Seek medical advice.
- Note to physician:** Treat symptomatically.

### 5. Fire-Fighting Measures

- Specific Hazards:** Low hazard heating can cause expansion or decomposition leading to violent rupture of containers. Fire dried residues may spatter upon contact with water. Keep containers cool with water spray. Only the dried residue will burn emitting acrid smoke and irritating fumes. If the dried residue has ignited, decomposition products may include: Carbon dioxide (CO<sub>2</sub>), and carbon monoxide (CO). Extinguish the fire using (CO<sub>2</sub>), dry chemical or foam. Fire fighters to use self contained breathing apparatus if risk of exposure to products of decomposition.

### 6. Accidental Release Measures

- Specific Hazards:** In the event of a large spill: Contact supplier/manufacturer. Isolate leaking containers and stop leak if safe to do so. Contain & prevent contamination of drains and waterways. Clean up using a shovel. Collect and seal in properly labelled drums for disposal. Normally suitable for disposal at approved land waste site. Wash away residues with water. In the event of a small spill: Scrape up, mop up and wash to drain with copious volumes of water. Wipe up residue with a cloth. Dispose of contaminated rags in a waste bin.

### 7. Handling and Storage

- Conditions for safe storage:** Store in cool, dry place. Store in original containers. Transport in original containers. Do not freeze, avoid storing on concrete during cold conditions.

# CRAFTERS CHOICE FABRIC GLUE

## Material Safety Data Sheet

### 8. Exposure Controls / Personal Protection

#### National Exposure Standards:

	TWA		STEL	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Toluene	100	377	150	565

**Other Exposure Information:** This product contains Toluene. The product (wet) odour may cause discomfort under the influence of elevated temperatures or in confined areas. The use of a solvent mask under these circumstances may be advisable. TOLUENE: OSHA PEL:TWA 200p.p.m. ; CL 300; Pk 500/10M ACGIH TLV:TWA 100p.p.m.; STEL 150 p.p.m.

**Engineering Controls:** Use in well ventilated areas. Keep containers in well ventilated area. Must be sufficient to prevent breathing of vapour. Local exhaust ventilation system may be required. Provide ventilation for 24 hours after use.

**Eye Protection:** Safety glasses, goggles or faceshield as appropriate

**Hand Protection:** PVC or rubber gloves

**Personal Protective Equipment:** Wearing of the following personal protective equipment may be advisable. Chemically resistant gloves. Avoid skin and eye contact. Avoid inhaling the vapour when working in a confined area.

**Hygiene Measures:** Wash contaminated clothing and protective equipment before storing/re-using. Always wash hands before smoking, eating, drinking or using the toilet.

### 9. Physical and chemical properties

<b>Form:</b>	Liquid
<b>Appearance:</b>	Thin white liquid with slight solvent odour
<b>Decomposition Temperature:</b>	Not Applicable
<b>Melting Point:</b>	Not Applicable
<b>Boiling Point:</b>	Initial Boiling Point: 100°C
<b>Solubility in water:</b>	Completely dispersible
<b>Specific Gravity:</b>	1.02 approx
<b>pH Value:</b>	Approx 7.0
<b>Volatile Component:</b>	Water
<b>Flash Point (°C):</b>	Not Applicable
<b>Flammability:</b>	Non flammable. Product residue, following evaporation of liquid content will burn in the presence of an ignition source.
<b>Auto Ignition Temperature:</b>	Not applicable
<b>Flammable Limits - Lower:</b>	Not applicable
<b>Explosion Properties:</b>	Not applicable
<b>Molecular Weight:</b>	Not applicable

# CRAFTERS CHOICE FABRIC GLUE

## Material Safety Data Sheet

### 10. Stability and Reactivity

Hazardous Reactions: CONDITIONS TO AVOID: Extreme heat greater than 100°C. INCOMPATIBLE MATERIALS: Strong oxidisers. HAZARDOUS POLYMERISATION: Will not occur.

### 11. Toxicological Information

**Ingestion:** May cause gastric irritation. Ingestion can cause nausea and vomiting.

**Inhalation:** Practically non-harmful by inhalation. May cause irritation to the nose and throat. Not normally an inhalation risk due to low vapour pressure at ambient temperatures.

**Eye contact:** A mild eye irritant. May cause watering of eyes. May cause soreness.

**Skin contact:** Repeated or prolonged skin contact may lead to irritation.

**Chronic Effects:**

Repeated or prolonged skin contact can cause chronic dermatitis

### 12. Ecological Information

Avoid contaminating waterways. Harmful to aquatic life.

### 13. Disposal Considerations

### 14. Transport Information

NOT classified as a Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG) for transport by Road and Rail, IMDG Code for transport by sea and by IATA Dangerous Code for air transport.

### 15. Regulatory Information

**Poisons Schedule:** Not Schedules

**Packaging & Labelling:** Not applicable

# **CRAFTERS CHOICE FABRIC GLUE**

## **Material Safety Data Sheet**

### **16. Other Information**

**Contact Point:** CSA Trading Pty Ltd

**Phone:** +61 3 9895 4333 (International)

**Fax:** +61 3 9899 4519 (International)

**After Hours:** Poisons Information Centre : 13 11 26 (Australia) 0800 764 766 (New Zealand)

The information and recommendations set down here in this document are presented in good faith and to the best of CSA Trading's knowledge. CSA Trading Pty Ltd cannot predict or control all conditions of use or handling of this product and each user must review this document in the context of the conditions under which they intend to handle and use this product. It is the responsibility of the user to ensure a proper assessment has been carried out. No representations or warranties, either expressed or implied, or merchantability, fitness for purpose or any other nature are made hereunder with respect to the product to which this information refers.